

# NXH80B120H2Q0

## Dual Boost Power Module

The NXH80B120H2Q0 is a high-density, integrated power module combines high-performance IGBTs with rugged anti-parallel diodes including on-board thermistor.

### Features

- Dual Boost 40 A / 1200 V IGBT + SiC Rectifier Hybrid Module
- 1200 V FSII IGBT  $V_{CE(SAT)} = 2.2$  V
- 1200 V SiC Diode  $V_F = 1.4$  V
- Low Inductive Layout
- Solderable Pins
- Thermistor
- Bare Copper and Nickel-Plated DBC Options

### Typical Applications

- Solar Inverter
- Uninterruptible Power Supplies
- Energy Storage Systems





Figure 1. NXH80B120H2Q0SG Schematic Diagram




ON Semiconductor®

[www.onsemi.com](http://www.onsemi.com)




Q0BOOST  
CASE 180AJ

### MARKING DIAGRAM



NXH80B120H2Q0Sxx = Device Code  
AT = Assembly & Test Site Code  
YYWW = Year and Work Week Code

### PIN CONNECTIONS



### ORDERING INFORMATION

See detailed ordering, marking and shipping information on page 4 of this data sheet.

# NXH80B120H2Q0

**Table 1. ABSOLUTE MAXIMUM RATINGS** (Note 1)  $T_J = 25^\circ\text{C}$  unless otherwise noted

| Rating                                                                                                         | Symbol       | Value    | Unit             |
|----------------------------------------------------------------------------------------------------------------|--------------|----------|------------------|
| <b>BOOST IGBT</b>                                                                                              |              |          |                  |
| Collector–Emitter Voltage                                                                                      | $V_{CES}$    | 1200     | V                |
| Gate–Emitter Voltage                                                                                           | $V_{GE}$     | $\pm 20$ | V                |
| Continuous Collector Current @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )                          | $I_C$        | 41       | A                |
| Pulsed Collector Current ( $T_J = 175^\circ\text{C}$ )                                                         | $I_{Cpulse}$ | 123      | A                |
| Maximum Power Dissipation @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )                             | $P_{tot}$    | 103      | W                |
| Short Circuit Withstand Time @ $V_{GE} = 15\text{ V}$ , $V_{CE} = 600\text{ V}$ , $T_J \leq 150^\circ\text{C}$ | $T_{sc}$     | 5        | $\mu\text{s}$    |
| Minimum Operating Junction Temperature                                                                         | $T_{JMIN}$   | $-40$    | $^\circ\text{C}$ |
| Maximum Operating Junction Temperature                                                                         | $T_{JMAX}$   | 150      | $^\circ\text{C}$ |

## BOOST DIODE

|                                                                                     |            |       |                      |
|-------------------------------------------------------------------------------------|------------|-------|----------------------|
| Peak Repetitive Reverse Voltage                                                     | $V_{RRM}$  | 1200  | V                    |
| Continuous Forward Current @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ ) | $I_F$      | 28    | A                    |
| Repetitive Peak Forward Current (limited by $T_J$ , duty cycle = 10%)               | $I_{FRM}$  | 75    | A                    |
| Maximum Power Dissipation @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )  | $P_{tot}$  | 79    | W                    |
| Surge Forward Current (60 Hz single half–sine wave) ( $T_J = 25^\circ\text{C}$ )    | $I_{FSM}$  | 69    | A                    |
| $I^2t$ – value (60 Hz single half–sine wave) ( $T_J = 150^\circ\text{C}$ )          | $I^2t$     | 19    | $\text{A}^2\text{s}$ |
| Minimum Operating Junction Temperature                                              | $T_{JMIN}$ | $-40$ | $^\circ\text{C}$     |
| Maximum Operating Junction Temperature                                              | $T_{JMAX}$ | 150   | $^\circ\text{C}$     |

## BYPASS DIODE / IGBT PROTECTION DIODE

|                                                                                             |            |       |                  |
|---------------------------------------------------------------------------------------------|------------|-------|------------------|
| Peak Repetitive Reverse Voltage                                                             | $V_{RRM}$  | 1600  | V                |
| Continuous Forward Current @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )         | $I_F$      | 46    | A                |
| Repetitive Peak Forward Current ( $T_J = 175^\circ\text{C}$ , $t_p$ limited by $T_{Jmax}$ ) | $I_{FRM}$  | 130   | A                |
| Power Dissipation Per Diode @ $T_h = 80^\circ\text{C}$ ( $T_J = 175^\circ\text{C}$ )        | $P_{tot}$  | 66    | W                |
| Minimum Operating Junction Temperature                                                      | $T_{JMIN}$ | $-40$ | $^\circ\text{C}$ |
| Maximum Operating Junction Temperature                                                      | $T_{JMAX}$ | 150   | $^\circ\text{C}$ |

## THERMAL PROPERTIES

|                           |           |                |                  |
|---------------------------|-----------|----------------|------------------|
| Storage Temperature range | $T_{stg}$ | $-40$ to $125$ | $^\circ\text{C}$ |
|---------------------------|-----------|----------------|------------------|

## INSULATION PROPERTIES

|                                                    |          |      |           |
|----------------------------------------------------|----------|------|-----------|
| Isolation test voltage, $t = 1\text{ sec}$ , 60 Hz | $V_{is}$ | 3000 | $V_{RMS}$ |
| Creepage distance                                  |          | 12.7 | mm        |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. Refer to ELECTRICAL CHARACTERISTICS, RECOMMENDED OPERATING RANGES and/or APPLICATION INFORMATION for Safe Operating parameters.

**Table 2. RECOMMENDED OPERATING RANGES**

| Rating                                | Symbol | Min   | Max               | Unit             |
|---------------------------------------|--------|-------|-------------------|------------------|
| Module Operating Junction Temperature | $T_J$  | $-40$ | $(T_{Jmax} - 25)$ | $^\circ\text{C}$ |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

# NXH80B120H2Q0

**Table 3. ELECTRICAL CHARACTERISTICS**  $T_J = 25^\circ\text{C}$  unless otherwise noted

| Parameter                                                 | Test Conditions                                                                                                        | Symbol        | Min | Typ  | Max | Unit               |
|-----------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|---------------|-----|------|-----|--------------------|
| <b>BOOST IGBT CHARACTERISTICS</b>                         |                                                                                                                        |               |     |      |     |                    |
| Collector-Emitter Cutoff Current                          | $V_{GE} = 0\text{ V}, V_{CE} = 1200\text{ V}$                                                                          | $I_{CES}$     | —   | —    | 200 | $\mu\text{A}$      |
| Collector-Emitter Saturation Voltage                      | $V_{GE} = 15\text{ V}, I_C = 40\text{ A}, T_J = 25^\circ\text{C}$                                                      | $V_{CE(sat)}$ | —   | 2.20 | 2.5 | V                  |
|                                                           | $V_{GE} = 15\text{ V}, I_C = 40\text{ A}, T_J = 150^\circ\text{C}$                                                     |               | —   | 2.16 | —   |                    |
| Gate-Emitter Threshold Voltage                            | $V_{GE} = V_{CE}, I_C = 1.5\text{ mA}$                                                                                 | $V_{GE(TH)}$  | —   | 5.45 | 6.4 | V                  |
| Gate Leakage Current                                      | $V_{GE} = 20\text{ V}, V_{CE} = 0\text{ V}$                                                                            | $I_{GES}$     | —   | —    | 200 | nA                 |
| Turn-on Delay Time                                        | $T_J = 25^\circ\text{C}$<br>$V_{CE} = 700\text{ V}, I_C = 40\text{ A}$<br>$V_{GE} = \pm 15\text{ V}, R_G = 4\ \Omega$  | $t_{d(on)}$   | —   | 27   | —   | ns                 |
| Rise Time                                                 |                                                                                                                        | $t_r$         | —   | 19   | —   |                    |
| Turn-off Delay Time                                       |                                                                                                                        | $t_{d(off)}$  | —   | 94   | —   |                    |
| Fall Time                                                 |                                                                                                                        | $t_f$         | —   | 78   | —   |                    |
| Turn-on Switching Loss per Pulse                          |                                                                                                                        | $E_{on}$      | —   | 540  | —   | $\mu\text{J}$      |
| Turn-off Switching Loss per Pulse                         |                                                                                                                        | $E_{off}$     | —   | 1640 | —   |                    |
| Turn-on Delay Time                                        | $T_J = 125^\circ\text{C}$<br>$V_{CE} = 700\text{ V}, I_C = 40\text{ A}$<br>$V_{GE} = \pm 15\text{ V}, R_G = 4\ \Omega$ | $t_{d(on)}$   | —   | 27   | —   | ns                 |
| Rise Time                                                 |                                                                                                                        | $t_r$         | —   | 20   | —   |                    |
| Turn-off Delay Time                                       |                                                                                                                        | $t_{d(off)}$  | —   | 110  | —   |                    |
| Fall Time                                                 |                                                                                                                        | $t_f$         | —   | 189  | —   |                    |
| Turn-on Switching Loss per Pulse                          |                                                                                                                        | $E_{on}$      | —   | 620  | —   | $\mu\text{J}$      |
| Turn-off Switching Loss per Pulse                         |                                                                                                                        | $E_{off}$     | —   | 3590 | —   |                    |
| Input Capacitance                                         | $V_{CE} = 25\text{ V}, V_{GE} = 0\text{ V}, f = 10\text{ kHz}$                                                         | $C_{ies}$     | —   | 9700 | —   | pF                 |
| Output Capacitance                                        |                                                                                                                        | $C_{oes}$     | —   | 200  | —   |                    |
| Reverse Transfer Capacitance                              |                                                                                                                        | $C_{res}$     | —   | 170  | —   |                    |
| Total Gate Charge                                         | $V_{CE} = 600\text{ V}, I_C = 40\text{ A}, V_{GE} = 15\text{ V}$                                                       | $Q_g$         | —   | 400  | —   | nC                 |
| Thermal Resistance – chip-to-heatsink                     | Thermal grease, Thickness < 100 $\mu\text{m}$ ,<br>$\lambda = 0.84\text{ W/mK}$                                        | $R_{thJH}$    | —   | 0.92 | —   | $^\circ\text{C/W}$ |
| <b>BOOST DIODE CHARACTERISTICS</b>                        |                                                                                                                        |               |     |      |     |                    |
| Diode Reverse Leakage Current                             | $V_R = 1200\text{ V}$                                                                                                  | $I_R$         | —   | —    | 300 | $\mu\text{A}$      |
| Diode Forward Voltage                                     | $I_F = 15\text{ A}, T_J = 25^\circ\text{C}$                                                                            | $V_F$         | —   | 1.42 | 1.7 | V                  |
|                                                           | $I_F = 15\text{ A}, T_J = 150^\circ\text{C}$                                                                           |               | —   | 1.95 | —   |                    |
| Reverse Recovery Time                                     | $T_J = 25^\circ\text{C}$<br>$V_{CE} = 700\text{ V}, I_C = 40\text{ A}$<br>$V_{GE} = \pm 15\text{ V}, R_G = 4\ \Omega$  | $t_{rr}$      | —   | 27   | —   | ns                 |
| Reverse Recovery Charge                                   |                                                                                                                        | $Q_{rr}$      | —   | 280  | —   | nC                 |
| Peak Reverse Recovery Current                             |                                                                                                                        | $I_{RRM}$     | —   | 16   | —   | A                  |
| Peak Rate of Fall of Recovery Current                     |                                                                                                                        | $di/dt$       | —   | 1080 | —   | A/ $\mu\text{s}$   |
| Reverse Recovery Energy                                   |                                                                                                                        | $E_{rr}$      | —   | 130  | —   | $\mu\text{J}$      |
| Reverse Recovery Time                                     | $T_J = 125^\circ\text{C}$<br>$V_{CE} = 700\text{ V}, I_C = 40\text{ A}$<br>$V_{GE} = \pm 15\text{ V}, R_G = 4\ \Omega$ | $t_{rr}$      | —   | 28   | —   | ns                 |
| Reverse Recovery Charge                                   |                                                                                                                        | $Q_{rr}$      | —   | 250  | —   | nC                 |
| Peak Reverse Recovery Current                             |                                                                                                                        | $I_{RRM}$     | —   | 15   | —   | A                  |
| Peak Rate of Fall of Recovery Current                     |                                                                                                                        | $di/dt$       | —   | 940  | —   | A/ $\mu\text{s}$   |
| Reverse Recovery Energy                                   |                                                                                                                        | $E_{rr}$      | —   | 110  | —   | $\mu\text{J}$      |
| Thermal Resistance – chip-to-heatsink                     | Thermal grease, Thickness < 100 $\mu\text{m}$ ,<br>$\lambda = 0.84\text{ W/mK}$                                        | $R_{thJH}$    | —   | 1.21 | —   | $^\circ\text{C/W}$ |
| <b>BYPASS DIODE/IGBT PROTECTION DIODE CHARACTERISTICS</b> |                                                                                                                        |               |     |      |     |                    |
| Diode Reverse Leakage Current                             | $V_R = 1600\text{ V}, T_J = 25^\circ\text{C}$                                                                          | $I_R$         | —   | —    | 100 | $\mu\text{A}$      |

# NXH80B120H2Q0

**Table 3. ELECTRICAL CHARACTERISTICS**  $T_J = 25^\circ\text{C}$  unless otherwise noted

| Parameter                                                 | Test Conditions                                                                 | Symbol     | Min | Typ  | Max | Unit               |
|-----------------------------------------------------------|---------------------------------------------------------------------------------|------------|-----|------|-----|--------------------|
| <b>BYPASS DIODE/IGBT PROTECTION DIODE CHARACTERISTICS</b> |                                                                                 |            |     |      |     |                    |
| Diode Forward Voltage                                     | $I_F = 25\text{ A}, T_J = 25^\circ\text{C}$                                     | $V_F$      | –   | 1.0  | 1.4 | V                  |
|                                                           | $I_F = 25\text{ A}, T_J = 150^\circ\text{C}$                                    |            | –   | 0.90 | –   |                    |
| Thermal Resistance – chip-to-heatsink                     | Thermal grease, Thickness < 100 $\mu\text{m}$ ,<br>$\lambda = 0.84\text{ W/mK}$ | $R_{thJH}$ | –   | 1.44 | –   | $^\circ\text{C/W}$ |

## THERMISTOR CHARACTERISTICS

|                            |                                   |              |    |      |   |                  |
|----------------------------|-----------------------------------|--------------|----|------|---|------------------|
| Nominal resistance         |                                   | $R_{25}$     | –  | 22   | – | $\text{k}\Omega$ |
| Nominal resistance         | $T = 100^\circ\text{C}$           | $R_{100}$    | –  | 1486 | – | $\Omega$         |
| Deviation of R25           |                                   | $\Delta R/R$ | –5 | –    | 5 | %                |
| Power dissipation          |                                   | $P_D$        | –  | 200  | – | mW               |
| Power dissipation constant |                                   |              | –  | 2    | – | mW/K             |
| B-value                    | $B(25/50)$ , tolerance $\pm 3\%$  |              | –  | 3950 | – | K                |
| B-value                    | $B(25/100)$ , tolerance $\pm 3\%$ |              | –  | 3998 | – | K                |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

## ORDERING INFORMATION

| Orderable Part Number | Marking          | Package                                                                             | Shipping                |
|-----------------------|------------------|-------------------------------------------------------------------------------------|-------------------------|
| NXH80B120H2Q0SG       | NXH80B120H2Q0SG  | Q0BOOST – Case 180AJ<br>Bare Copper DBC, Solder Pins<br>(Pb-Free and Halide-Free)   | 24 Units / Blister Tray |
| NXH80B120H2Q0SNG      | NXH80B120H2Q0SNG | Q0BOOST – Case 180AJ<br>Nickel-Plated DBC, Solder Pins<br>(Pb-Free and Halide-Free) | 24 Units / Blister Tray |

TYPICAL CHARACTERISTICS – Boost IGBT & Boost Diode




Figure 1. IGBT Typical Output Characteristics




Figure 2. IGBT Typical Output Characteristics




Figure 3. IGBT Typical Transfer Characteristics




Figure 4. Diode Forward Characteristic




Figure 5. Typical Turn On Loss vs.  $I_C$




Figure 6. Typical Turn Off Loss vs.  $I_C$

TYPICAL CHARACTERISTICS – Boost IGBT & Boost Diode




Figure 7. Typical Switching Times vs.  $I_C$




Figure 8. Typical Switching Times vs.  $I_C$




Figure 9. Typical Reverse Recovery Time vs.  $I_C$




Figure 10. Typical Reverse Recovery Charge vs.  $I_C$




Figure 11. Typical Reverse Recovery Peak Current vs.  $I_C$






Figure 12. Typical Diode Current Slope vs.  $I_C$

# NXH80B120H2Q0


## TYPICAL CHARACTERISTICS – Boost IGBT & Boost Diode




**Figure 13. Typical Reverse Recovery Energy vs.  $I_C$**



**Figure 14. Gate Voltage vs. Gate Charge**



**Figure 15. IGBT Transient Thermal Impedance**



**Figure 16. Diode Transient Thermal Impedance Boost Diode**

# NXH80B120H2Q0

## TYPICAL CHARACTERISTICS – Boost IGBT & Boost Diode




Figure 17. T1 & T2 FBSOA




Figure 18. T1 & T2 RBSOA

## NXH80B120H2Q0

### TYPICAL CHARACTERISTICS – IGBT Protection Diode and Bypass Diode




Figure 19. Diode Forward Characteristic




Figure 20. Diode Transient Thermal Impedance Bypass Diode / IGBT Protection Diode

### TYPICAL CHARACTERISTICS – Thermistor




Figure 21. Thermistor Characteristic



# MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS

ON Semiconductor®



## PIM22, 55x32.5 / Q0BOOST CASE 180AJ ISSUE B

DATE 08 NOV 2017



### NOTES:

1. DIMENSIONING AND TOLERANCING PER. ASME Y14.5M, 2009.
2. CONTROLLING DIMENSION: MILLIMETERS
3. DIMENSION b APPLIES TO THE PLATED TERMINALS AND IS MEASURED BETWEEN 1.00 AND 3.00 FROM THE TERMINAL TIP.
4. POSITION OF THE CENTER OF THE TERMINALS IS DETERMINED FROM DATUM B THE CENTER OF DIMENSION D, X DIRECTION, AND FROM DATUM A, Y DIRECTION. POSITIONAL TOLERANCE, AS NOTED IN DRAWING, APPLIES TO EACH TERMINAL IN BOTH DIRECTIONS.
5. PACKAGE MARKING IS LOCATED AS SHOWN ON THE SIDE OPPOSITE THE PACKAGE ORIENTATION FEATURES.


| DIM | MILLIMETERS |       |
|-----|-------------|-------|
|     | MIN.        | NDM.  |
| A   | 13.50       | 13.90 |
| A1  | 0.10        | 0.30  |
| A2  | 11.50       | 11.90 |
| A3  | 15.65       | 16.05 |
| A4  | 16.35       | REF   |
| b   | 0.95        | 1.05  |
| D   | 54.80       | 55.20 |
| D1  | 65.60       | 66.20 |
| E   | 32.20       | 32.80 |
| P   | 4.20        | 4.40  |
| P1  | 8.90        | 9.10  |

### MOUNTING HOLE POSITION

NOTE 4

| HOLE POSITION |        |        | PIN POSITION |        |       | PIN POSITION |        |       | PIN POSITION |        |        | PIN POSITION |        |        |
|---------------|--------|--------|--------------|--------|-------|--------------|--------|-------|--------------|--------|--------|--------------|--------|--------|
| PIN           | X      | Y      | PIN          | X      | Y     | PIN          | X      | Y     | PIN          | X      | Y      | PIN          | X      | Y      |
| 1             | -16.75 | -11.25 | 12           | 16.75  | 6.55  | 1            | -16.75 | 11.25 | 12           | 16.75  | -6.55  | 1            | -16.75 | -11.25 |
| 2             | -13.85 | -11.25 | 13           | 15.25  | 11.25 | 2            | -13.85 | 11.25 | 13           | 15.25  | -11.25 | 2            | -13.85 | -11.25 |
| 3             | -8.45  | -11.25 | 14           | 12.35  | 11.25 | 3            | -8.45  | 11.25 | 14           | 12.35  | -11.25 | 3            | -8.45  | -11.25 |
| 4             | -5.95  | -11.25 | 15           | 5.35   | 11.25 | 4            | -5.95  | 11.25 | 15           | 5.35   | -11.25 | 4            | -5.95  | -11.25 |
| 5             | 2.85   | -11.25 | 16           | 2.85   | 11.25 | 5            | 2.85   | 11.25 | 16           | 2.85   | -11.25 | 5            | 2.85   | -11.25 |
| 6             | 5.35   | -11.25 | 17           | -5.95  | 11.25 | 6            | 5.35   | 11.25 | 17           | -5.95  | -11.25 | 6            | 5.35   | -11.25 |
| 7             | 12.35  | -11.25 | 18           | -8.45  | 11.25 | 7            | 12.35  | 11.25 | 18           | -8.45  | -11.25 | 7            | 12.35  | -11.25 |
| 8             | 15.25  | -11.25 | 19           | -13.85 | 11.25 | 8            | 15.25  | 11.25 | 19           | -13.85 | -11.25 | 8            | 15.25  | -11.25 |
| 9             | 16.75  | -6.55  | 20           | -16.75 | 11.25 | 9            | 16.75  | 6.55  | 20           | -16.75 | -11.25 | 9            | 16.75  | -6.55  |
| 10            | 16.75  | -4.05  | 21           | -16.75 | 3.25  | 10           | 16.75  | 4.05  | 21           | -16.75 | -3.25  | 10           | 16.75  | -4.05  |
| 11            | 16.75  | 4.05   | 22           | -16.75 | -3.25 | 11           | 16.75  | -4.05 | 22           | -16.75 | 3.25   | 11           | 16.75  | -4.05  |

### GENERIC MARKING DIAGRAM\*



XXXXX = Specific Device Code  
G = Pb-Free Package  
AT = Assembly & Test Site Code  
YYWW = Year and Work Week Code





\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "•", may or may not be present. Some products may not follow the Generic Marking.

|                  |                                      |                                                                                                                                                                                  |
|------------------|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98AON63481G                          | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | PIM22 55X32.5 / Q0BOOST (SOLDER PIN) | PAGE 1 OF 2                                                                                                                                                                      |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**PIM22, 55x32.5 / Q0BOOST**  
CASE 180AJ  
ISSUE B

DATE 08 NOV 2017



MOUNTING HOLE DETAIL

|                         |                                             |                                                                                                                                                                                  |
|-------------------------|---------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98AON63481G</b>                          | Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>PIM22 55X32.5 / Q0BOOST (SOLDER PIN)</b> | <b>PAGE 2 OF 2</b>                                                                                                                                                               |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi Website:** [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

**North American Technical Support:**

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative