onsemi

AR0135AT

CMOS Image Sensor, 1.2 MP, 1/3", Global Shutter

Product Overview

For complete documentation, see the data sheet.

This 1/3-inch format, 1.2 MP imaging device has been designed to address the challenging requirements of automotive in-cabin cameras. The new global shutter sensor allows the camera to "freeze" fast moving scene data, and ensures effective synchronization with pulsed light sources. The AR0135AT sensor incorporates a new innovative global shutter pixel design, with 10X lower dark current and 4X higher shutter efficiency vs. previous generation products. These improvements allow the sensor to produce clear, low-noise images, in both low-light and bright scenes, and in high temperature environments. This performance enables the required eye tracking and gesture detection functionality in next generation automotive in-cabin systems.

Features

- ON Semiconductor's Next Generation Global Shutter Technology
- Superior Low-light Performance
- HD Video (720p60)
- Video/Single Frame Mode
- Flexible Row-skip Modes
- On-chip AE and Statistics Engine
- Parallel and Serial Output
- Support for External LED or Flash
- Auto Black Level Calibration
- Context Switching For more features, see the data sheet

Applications

- Automotive In-Cabin / Driver Monitoring System
- 720p60 Video Applications

End Products

Drivind Monitoring System

Part Electrical Specifications												
Product	Pricing (\$/Unit)	Complian ce	Status	Туре	Megapi xels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interfac e	Color	Packag e Type
AR0135AT2M00 XUEA0-DPBR		APPH	Active									IBGA- 63
AR0135AT2M00 XUEA0-DRBR		APPH	Active	CMOS	1.2	54	1/3 inch	Global Shutter	3.75 x 3.75		Mono	IBGA- 63
AR0135AT2M00 XUEA0-TPBR		A P Pb H	Active	CMOS	1.2	54	1/3 inch	Global Shutter	3.75 x 3.75		Mono	IBGA- 63
AR0135AT2M25 XUEA0-DPBR		A P Pb H	Active	CMOS	1.2	54	1/3 inch	Global Shutter	3.75 x 3.75		Mono	IBGA- 63
AR0135AT2M25 XUEA0-DRBR		A P Pb H	Active	CMOS	1.2	54	1/3 inch	Global Shutter	3.75 x 3.75		Mono	IBGA- 63
AR0135AT2M25 XUEA0-TPBR		A P Pb H	Active	CMOS	1.2	54	1/3 inch	Global Shutter	3.75 x 3.75		Mono	IBGA- 63
AR0135AT2M25 XUEA0-TRBR		APPH	Active	CMOS	1.2	54	1/3 inch	Global Shutter	3.75 x 3.75		Mono	IBGA- 63