

AR1820HS

CMOS Image Sensor, 18 MP, 1/2.3"

Product Overview

For complete documentation, see the data sheet.

The AR1820HS is an 18 megapixel, 1/2.3-inch format, 1.25 um pixel sensor using ON Semiconductor's A-PixHS™ BSI technology. With a variety of operating modes, the AR1820HS can dynamically optimize resolution, low-light and frame rate for environmental conditions. For example, the camera could run in full 18 megapixel resolution at 24 fps under high-light conditions, and switch to a 2:1 summing and 2:1 binning at 1080p 60 frames-per-second mode for superb low-light performance under darker conditions. With high resolution and frame rates, and a variety of flexible modes, the AR1820HS sensor is excellent for many applications such as surveillance, sports cameras and mobile handsets.

Applications

- Camera
- Security

Part Electrical Specifications												
Product	Pricing (\$/Unit)	Complian ce	Status	Туре	Megapi xels	Frame Rate (fps)	Optical Format	Shutter Type	Pixel Size (µm)	Output Interfac e	Color	Packag e Type
AR1820HSSC00 SHEA0-DP1		Pb H	Active	CMOS	18.1	24	1/2.3 inch	Electron ic Rolling	1.25 x 1.25		RGB	IBGA- 60
AR1820HSSC00 SHEA0-DR		Pb H	Active	CMOS	18.1	24	1/2.3 inch	Electron ic Rolling	1.25 x 1.25		RGB	IBGA- 60
AR1820HSSC12 SHEA0-DP		РЬ Н	Active	CMOS	18.1	24	1/2.3 inch	Electron ic Rolling	1.25 x 1.25		RGB	IBGA- 60
AR1820HSSC12 SHEA0-DP1		РЬ Н	Active	CMOS	18.1	24	1/2.3 inch	Electron ic Rolling	1.25 x 1.25		RGB	IBGA- 60
AR1820HSSC12 SHEA0-DR		Pb H	Active	CMOS	18.1	24	1/2.3 inch	Electron ic Rolling	1.25 x 1.25		RGB	IBGA- 60
AR1820HSSC12 SHEA0-DR1		РЬ Н	Active	CMOS	18.1	24	1/2.3 inch	Electron ic Rolling	1.25 x 1.25		RGB	IBGA- 60
AR1820HSSC12 SMD20		РЬ Н	Active	CMOS	18.1	24	1/2.3 inch	Electron ic Rolling	1.25 x 1.25		RGB	