

# 1 $\Omega$ SPDT Switch

## NL5S4157A

The NL5S4157A is a low  $R_{ON}$  SPDT analog switch. The device is designed for low operating voltage, high current switching of speaker output for mobile applications. It can switch a balanced stereo output. It can handle a balanced microphone/speaker/ringtone generator in monophone mode.

### Features

- Wide  $V_{CC}$  Operating Range: 1.65 V to 5.5 V
- OVT up to +5.5 V for Control pin
- $R_{ON}$ : Typically  $< 1 \Omega$  at  $V_{CC} = 4.5$  V
- Rail-to-Rail Input/Output
- This Device is Pb-Free, Halogen Free/BFR Free and is RoHS Compliant

### Typical Applications

- Cell Phone Speaker/Microphone Switching
- Ringtone-Chip/Amplifier Switching
- Stereo Balanced (Push-Pull) Switching
- RF PA Routing
- General Switching




**ON Semiconductor®**

[www.onsemi.com](http://www.onsemi.com)



SC-88/SC70-6/SOT-363  
CASE 419B-02

### MARKING DIAGRAM



AT = Specific Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.

### ORDERING INFORMATION

See detailed ordering and shipping information on page 6 of this data sheet.

# NL5S4157A

## PIN ASSIGNMENTS




Figure 1. NL5S4157A (Top View)




Figure 2. Analog Symbol

## PIN DESCRIPTION

| Pin | Name            | Description          |
|-----|-----------------|----------------------|
| 1   | NO              | Normally-Open Port   |
| 2   | GND             | Supply Ground        |
| 3   | NC              | Normally-Closed Port |
| 4   | COM             | Common Port          |
| 5   | V <sub>CC</sub> | Supply               |
| 6   | IN              | Switch Select Input  |

## FUNCTION TABLE

| IN | Switch    |
|----|-----------|
| L  | NC to COM |
| H  | NO to COM |

## MAXIMUM RATINGS

| Symbol       | Rating                                             | Value                | Unit |
|--------------|----------------------------------------------------|----------------------|------|
| $V_{CC}$     | Positive DC Supply Voltage                         | -0.5 to +6.0         | V    |
| $V_{IS}$     | Switch Input / Output Voltage                      | -0.5 to $V_{CC}+0.5$ | V    |
| $V_{IN}$     | Digital Select Input Voltage                       | -0.5 to +6.0         | V    |
| $I_{OK}$     | I/O Port Diode Current                             | $\pm 100$            | mA   |
| $I_{IK}$     | Select Input Diode Current                         | -100                 | mA   |
| $I_{I/O}$    | Continuous DC Current Through Analog Switch        | $\pm 100$            | mA   |
| $I_{I/O-pk}$ | Peak Current Through Analog Switch, 10% Duty Cycle | $\pm 300$            | mA   |
| $T_s$        | Storage Temperature                                | -65 to +150          | °C   |
| ESD          | Human Body Model (HBM)                             | 2                    | kV   |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

## RECOMMENDED OPERATING CONDITIONS

| Symbol     | Parameter                                               |                            | Min  | Max      | Unit |
|------------|---------------------------------------------------------|----------------------------|------|----------|------|
| $V_{CC}$   | Positive DC Supply Voltage                              |                            | 1.65 | 5.5      | V    |
| $V_{IS}$   | Switch Input / Output Voltage                           |                            | GND  | $V_{CC}$ | V    |
| $V_{IN}$   | Digital Select Input Voltage                            |                            | GND  | 5.5      | V    |
| $T_A$      | Operating Temperature Range                             |                            | -40  | +125     | °C   |
| $t_r, t_f$ | Input Transition Rise or Fall Time<br>(Select Input IN) | $V_{CC} \leq 3.0\text{ V}$ | 0    | 20       | ns/V |
|            |                                                         | $V_{CC} > 3.0\text{ V}$    | 0    | 10       |      |

Functional operation above the stresses listed in the Recommended Operating Ranges is not implied. Extended exposure to stresses beyond the Recommended Operating Ranges limits may affect device reliability.

ELECTRICAL CHARACTERISTICS

| Symbol              | Parameter                        | Condition                                                                                                                  | V <sub>CC</sub> (V) | Guaranteed Limit |     |      |               |      |                |      | Unit |
|---------------------|----------------------------------|----------------------------------------------------------------------------------------------------------------------------|---------------------|------------------|-----|------|---------------|------|----------------|------|------|
|                     |                                  |                                                                                                                            |                     | 25°C             |     |      | –40°C to 85°C |      | –40°C to 125°C |      |      |
|                     |                                  |                                                                                                                            |                     | Min              | Typ | Max  | Min           | Max  | Min            | Max  |      |
| V <sub>IH</sub>     | Input High Voltage               |                                                                                                                            | 2.7                 | 1.1              |     |      | 1.1           |      | 1.1            |      | V    |
|                     |                                  |                                                                                                                            | 5.0                 | 1.42             |     |      | 1.42          |      | 1.42           |      |      |
| V <sub>IL</sub>     | Input Low Voltage                |                                                                                                                            | 2.7                 |                  |     | 0.4  |               | 0.4  |                | 0.4  | V    |
|                     |                                  |                                                                                                                            | 5.0                 |                  |     | 0.7  |               | 0.7  |                | 0.7  |      |
| I <sub>IN</sub>     | Input Leakage Current            | V <sub>IN</sub> = 0 V to 5.5 V                                                                                             | 1.65 – 5.5          |                  |     | ±0.1 |               | ±1   |                | ±1   | µA   |
| I <sub>OFF</sub>    | Input Leakage Current            | V <sub>IN</sub> = 0 to 5.5 V                                                                                               | 0                   |                  |     | 0.05 |               | 1    |                | 1    | µA   |
| I <sub>S(ON)</sub>  | ON-State Switch Leakage Current  | V <sub>IS</sub> = GND to V <sub>CC</sub> , V <sub>OS</sub> = Open                                                          | 5.5                 |                  |     | ±10  |               | ±200 |                | ±600 | nA   |
| I <sub>S(OFF)</sub> | OFF-State Switch Leakage Current | V <sub>IS</sub> = V <sub>CC</sub> and V <sub>OS</sub> = GND, or I <sub>S</sub> = GND and V <sub>OS</sub> = V <sub>CC</sub> | 5.5                 |                  |     | ±10  |               | ±200 |                | ±600 | nA   |
| I <sub>CC</sub>     | Quiescent Supply Current         | V <sub>IN</sub> = V <sub>CC</sub> or GND, I <sub>OS</sub> = 0 mA                                                           | 5.5                 |                  |     | 0.5  |               | 5    |                | 5    | µA   |

ANALOG SWITCH CHARACTERISTICS

| Symbol                               | Parameter                  | Condition                                                                                  | V <sub>CC</sub> (V) | Guaranteed Limit |       |      |                |      | Unit |
|--------------------------------------|----------------------------|--------------------------------------------------------------------------------------------|---------------------|------------------|-------|------|----------------|------|------|
|                                      |                            |                                                                                            |                     | 25°C             |       |      | –40°C to 125°C |      |      |
|                                      |                            |                                                                                            |                     | Min              | Typ   | Max  | Min            | Max  |      |
| R <sub>ON</sub><br>(Note 1)          | Switch ON Resistance       | V <sub>IS</sub> = 0 to V <sub>CC</sub> ,<br>I <sub>O</sub> = 100 mA                        | 2.7                 |                  | 0.9   | 1.2  |                | 1.4  | Ω    |
|                                      |                            |                                                                                            | 4.5                 |                  | 0.6   | 0.8  |                | 1.0  |      |
| ΔR <sub>ON</sub><br>(Notes 1, 2, 3)  | ON Resistance Match        | V <sub>IS</sub> = 1.5 V,<br>I <sub>A</sub> = 100 mA                                        | 2.7                 |                  | 0.05  | 0.15 |                | 0.15 | Ω    |
|                                      | Between Channels           | V <sub>IS</sub> = 2.5 V,<br>I <sub>A</sub> = 100 mA                                        | 4.5                 |                  | 0.04  | 0.12 |                | 0.15 |      |
| R <sub>FLAT</sub><br>(Notes 1, 2, 4) | ON Resistance Flatness     | V <sub>IS</sub> = 0 to V <sub>CC</sub> ,<br>I <sub>O</sub> = 100 mA                        | 2.7                 |                  | 0.3   | 0.4  |                | 0.4  | Ω    |
|                                      |                            |                                                                                            | 4.5                 |                  | 0.2   | 0.4  |                | 0.4  |      |
| Q<br>(Note 5)                        | Charge Injection           | C <sub>L</sub> = 1 nF,<br>V <sub>GEN</sub> = 0 V,                                          | 2.7                 |                  | 38    |      |                |      | pC   |
|                                      |                            | R <sub>GEN</sub> = 0 Ω                                                                     | 4.5                 |                  | 55    |      |                |      |      |
| V <sub>ISO</sub><br>(Note 6)         | Off–Isolation              | R <sub>L</sub> = 50 Ω,<br>f = 1 MHz                                                        | 2.7 – 5.5           |                  | –66   |      |                |      | dB   |
| V <sub>CT</sub>                      | Crosstalk                  | R <sub>L</sub> = 50 Ω,<br>f = 1 MHz                                                        | 2.7 – 5.5           |                  | –66   |      |                |      | dB   |
| BW                                   | –3 dB Bandwidth            | R <sub>L</sub> = 50 Ω                                                                      | 2.7 – 5.5           |                  | 57    |      |                |      | MHz  |
| THD<br>(Note 5)                      | Total Harmonic Distortion  | R <sub>L</sub> = 600 Ω,<br>V <sub>IS</sub> = 0.5 V <sub>P–P</sub> ,<br>f = 20 Hz to 20 kHz | 2.7 – 5.5           |                  | 0.004 |      |                |      | %    |
| C <sub>I</sub>                       | Select Input Capacitance   | f = 1 MHz                                                                                  | 0                   |                  | 3.0   |      |                |      | pF   |
| C <sub>OFF</sub>                     | NC/NO Port Off Capacitance | f = 1 MHz                                                                                  | 4.5                 |                  | 23    |      |                |      | pF   |
| C <sub>ON</sub>                      | COM Port ON Capacitance    | f = 1 MHz                                                                                  | 4.5                 |                  | 93    |      |                |      | pF   |

1. Measured by the voltage drop between NC/NO and COM pins at the indicated current through the switch. On Resistance is determined by the lower of the voltages on the two (NO, NC, COM).
2. Parameter is characterized but not tested in production.
3. ΔR<sub>ON</sub> = R<sub>ON</sub> max – R<sub>ON</sub> min measured at identical V<sub>CC</sub>, temperature and voltage levels.
4. Flatness is defined as the difference between the maximum and minimum value of On Resistance over the specified range of conditions.
5. Guaranteed by Design.
6. V<sub>ISO</sub> = 20 log<sub>10</sub> [V<sub>COM</sub>/V<sub>NO,NC</sub>].

## SWITCHING CHARACTERISTICS

| Symbol                       | Parameter                           | Condition                                            | V <sub>CC</sub> (V) | Guaranteed Limit |     |     |                |     | Unit |
|------------------------------|-------------------------------------|------------------------------------------------------|---------------------|------------------|-----|-----|----------------|-----|------|
|                              |                                     |                                                      |                     | 25°C             |     |     | −40°C to 125°C |     |      |
|                              |                                     |                                                      |                     | Min              | Typ | Max | Min            | Max |      |
| t <sub>PD</sub><br>(Note 7)  | Propagation Delay                   | V <sub>IN</sub> = V <sub>IH</sub> or V <sub>IL</sub> | 2.7                 |                  |     | 2.0 |                | 2.0 | ns   |
|                              |                                     |                                                      | 4.5                 |                  |     | 0.3 |                | 0.3 |      |
| t <sub>ON</sub>              | Turn-on Time,<br>(COM to NO or NC)  | R <sub>L</sub> = 50 Ω,<br>C <sub>L</sub> = 35 pF,    |                     |                  |     |     |                |     | ns   |
|                              |                                     | V <sub>IS</sub> = 1.5 V                              | 2.7                 |                  |     | 30  |                | 35  |      |
|                              |                                     | V <sub>IS</sub> = 3.0 V                              | 4.5                 |                  |     | 20  |                | 25  |      |
|                              |                                     | R <sub>L</sub> = 50 Ω,<br>C <sub>L</sub> = 100 pF,   |                     |                  |     |     |                |     |      |
|                              |                                     | V <sub>IS</sub> = 1.5 V                              | 3.3                 |                  |     | 100 |                | 100 |      |
| t <sub>OFF</sub>             | Turn-off Time,<br>(COM to NO or NC) | R <sub>L</sub> = 50 Ω,<br>C <sub>L</sub> = 35 pF,    |                     |                  |     |     |                |     | ns   |
|                              |                                     | V <sub>IS</sub> = 1.5 V                              | 2.7                 |                  |     | 20  |                | 25  |      |
|                              |                                     | V <sub>IS</sub> = 3.0 V                              | 4.5                 |                  |     | 15  |                | 20  |      |
|                              |                                     | R <sub>L</sub> = 50 Ω,<br>C <sub>L</sub> = 100 pF,   |                     |                  |     |     |                |     |      |
|                              |                                     | V <sub>IS</sub> = 1.5 V                              | 3.3                 |                  |     | 100 |                | 100 |      |
| T <sub>BBM</sub><br>(Note 5) | Break Before Make Time              | R <sub>L</sub> = 50 Ω,<br>C <sub>L</sub> = 35 pF     | 2.7                 | 0.5              |     |     | 0.5            |     | ns   |
|                              |                                     |                                                      | 4.5                 | 0.5              |     |     | 0.5            |     |      |

7. This parameter is guaranteed by design but not tested. The bus switch contributes no propagation delay other than the RC delay of the On Resistance of the switch and the 50 pF load capacitance, when driven by an ideal voltage source (zero output impedance).

## ORDERING INFORMATION

| Device         | Package                    | Marking | Pin 1 Orientation<br>(See below) | Shipping <sup>†</sup> |
|----------------|----------------------------|---------|----------------------------------|-----------------------|
| NL5S4157ADFT2G | SC – 88/SC70 – 6/SOT – 363 | AT      | Q4                               | 3000 / Tape & Reel    |

<sup>†</sup>For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

## PIN 1 ORIENTATION IN TAPE AND REEL

Pin 1 Orientation in Tape and Reel  
Direction of Feed




Figure 3.

## Test Setups





Figure 4.  $t_{BMM}$  (Time Break-Before-Make)






Figure 5.  $t_{ON}/t_{OFF}$



### Test Set-Up





Figure 6.  $t_{ON}/t_{OFF}$




Channel switch control/s test socket is normalized. Off isolation is measured across an off channel. Crosstalk is measured from an off channel to an on channel. On loss is the bandwidth of an On switch.  $V_{ISO}$ ,  $V_{CT}$ , Bandwidth and  $V_{ONL}$  are independent of the input signal direction.

$V_{ISO}$  or  $V_{CT}$  = Off Channel Isolation or crosstalk =  $20 \text{ Log for } V_{OUT} / V_{IN}$

$V_{ONL}$  = On Channel Loss =  $20 \text{ Log for } V_{OUT} / V_{IN}$  at 100 kHz to 50 MHz

Bandwidth (BW) = the frequency 3 dB below  $V_{ONL}$

**Figure 7. Off Channel Isolation/On Channel Loss (BW)/Crosstalk (On Channel to Off Channel)/ $V_{ONL}$**



**Figure 8. Charge Injection: (Q)**



TYPICAL CHARACTERISTICS




Figure 9.  $V_{ISO}$  vs. Frequency  
@  $V_{CC} = 4.5\text{ V}$




Figure 10. Bandwidth vs. Frequency




Figure 11. Total Harmonic Distortion




Figure 12. ON Resistance vs. Switch Voltage  
@  $V_{CC} = 2.7\text{ V}$




Figure 13. ON Resistance vs. Switch Voltage  
@  $V_{CC} = 4.5\text{ V}$




Figure 14. ON Resistance vs. Switch Voltage

# MECHANICAL CASE OUTLINE PACKAGE DIMENSIONS


ON Semiconductor®



SCALE 2:1

SC-88/SC70-6/SOT-363  
CASE 419B-02  
ISSUE Y


DATE 11 DEC 2012



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ASME Y14.5M, 1994.
  2. CONTROLLING DIMENSION: MILLIMETERS.
  3. DIMENSIONS D AND E1 DO NOT INCLUDE MOLD FLASH, PROTRUSIONS, OR GATE BURRS. MOLD FLASH, PROTRUSIONS, OR GATE BURRS SHALL NOT EXCEED 0.20 PER END.
  4. DIMENSIONS D AND E1 AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY AND DATUM H.
  5. DATUMS A AND B ARE DETERMINED AT DATUM H.
  6. DIMENSIONS b AND c APPLY TO THE FLAT SECTION OF THE LEAD BETWEEN 0.08 AND 0.15 FROM THE TIP.
  7. DIMENSION b DOES NOT INCLUDE DAMBAR PROTRUSION. ALLOWABLE DAMBAR PROTRUSION SHALL BE 0.08 TOTAL IN EXCESS OF DIMENSION b AT MAXIMUM MATERIAL CONDITION. THE DAMBAR CANNOT BE LOCATED ON THE LOWER RADIUS OF THE FOOT.

| DIM | MILLIMETERS |      |      | INCHES    |       |       |
|-----|-------------|------|------|-----------|-------|-------|
|     | MIN         | NOM  | MAX  | MIN       | NOM   | MAX   |
| A   | ---         | ---  | 1.10 | ---       | ---   | 0.043 |
| A1  | 0.00        | ---  | 0.10 | 0.000     | ---   | 0.004 |
| A2  | 0.70        | 0.90 | 1.00 | 0.027     | 0.035 | 0.039 |
| b   | 0.15        | 0.20 | 0.25 | 0.006     | 0.008 | 0.010 |
| C   | 0.08        | 0.15 | 0.22 | 0.003     | 0.006 | 0.009 |
| D   | 1.80        | 2.00 | 2.20 | 0.070     | 0.078 | 0.086 |
| E   | 2.00        | 2.10 | 2.20 | 0.078     | 0.082 | 0.086 |
| E1  | 1.15        | 1.25 | 1.35 | 0.045     | 0.049 | 0.053 |
| e   | 0.65 BSC    |      |      | 0.026 BSC |       |       |
| L   | 0.26        | 0.36 | 0.46 | 0.010     | 0.014 | 0.018 |
| L2  | 0.15 BSC    |      |      | 0.006 BSC |       |       |
| aaa | 0.15        |      |      | 0.006     |       |       |
| bbb | 0.30        |      |      | 0.012     |       |       |
| ccc | 0.10        |      |      | 0.004     |       |       |
| ddd | 0.10        |      |      | 0.004     |       |       |

## GENERIC MARKING DIAGRAM\*




XXX = Specific Device Code  
M = Date Code\*  
▪ = Pb-Free Package

(Note: Microdot may be in either location)

\*Date Code orientation and/or position may vary depending upon manufacturing location.

\*This information is generic. Please refer to device data sheet for actual part marking. Pb-Free indicator, "G" or microdot "▪", may or may not be present. Some products may not follow the Generic Marking.

## RECOMMENDED SOLDERING FOOTPRINT\*



\*For additional information on our Pb-Free strategy and soldering details, please download the ON Semiconductor Soldering and Mounting Techniques Reference Manual, SOLDERRM/D.

## STYLES ON PAGE 2

|                  |                      |                                                                                                                                                                                     |
|------------------|----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DOCUMENT NUMBER: | 98ASB42985B          | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| DESCRIPTION:     | SC-88/SC70-6/SOT-363 | PAGE 1 OF 2                                                                                                                                                                         |

ON Semiconductor and are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**SC-88/SC70-6/SOT-363**  
**CASE 419B-02**  
**ISSUE Y**

DATE 11 DEC 2012

|                                                                                                            |                                                                                                        |                                                                                                             |                                                                                                             |                                                                                                             |                                                                                                       |
|------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------|
| STYLE 1:<br>PIN 1. EMITTER 2<br>2. BASE 2<br>3. COLLECTOR 1<br>4. EMITTER 1<br>5. BASE 1<br>6. COLLECTOR 2 | STYLE 2:<br>CANCELLED                                                                                  | STYLE 3:<br>CANCELLED                                                                                       | STYLE 4:<br>PIN 1. CATHODE<br>2. CATHODE<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE<br>6. ANODE               | STYLE 5:<br>PIN 1. ANODE<br>2. ANODE<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE<br>6. CATHODE                 | STYLE 6:<br>PIN 1. ANODE 2<br>2. N/C<br>3. CATHODE 1<br>4. ANODE 1<br>5. N/C<br>6. CATHODE 2          |
| STYLE 7:<br>PIN 1. SOURCE 2<br>2. DRAIN 2<br>3. GATE 1<br>4. SOURCE 1<br>5. DRAIN 1<br>6. GATE 2           | STYLE 8:<br>CANCELLED                                                                                  | STYLE 9:<br>PIN 1. EMITTER 2<br>2. EMITTER 1<br>3. COLLECTOR 1<br>4. BASE 1<br>5. BASE 2<br>6. COLLECTOR 2  | STYLE 10:<br>PIN 1. SOURCE 2<br>2. SOURCE 1<br>3. GATE 1<br>4. DRAIN 1<br>5. DRAIN 2<br>6. GATE 2           | STYLE 11:<br>PIN 1. CATHODE 2<br>2. CATHODE 2<br>3. ANODE 1<br>4. CATHODE 1<br>5. CATHODE 1<br>6. ANODE 2   | STYLE 12:<br>PIN 1. ANODE 2<br>2. ANODE 2<br>3. CATHODE 1<br>4. ANODE 1<br>5. ANODE 1<br>6. CATHODE 2 |
| STYLE 13:<br>PIN 1. ANODE<br>2. N/C<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE<br>6. CATHODE                 | STYLE 14:<br>PIN 1. VREF<br>2. GND<br>3. GND<br>4. IOUT<br>5. VEN<br>6. VCC                            | STYLE 15:<br>PIN 1. ANODE 1<br>2. ANODE 2<br>3. ANODE 3<br>4. CATHODE 3<br>5. CATHODE 2<br>6. CATHODE 1     | STYLE 16:<br>PIN 1. BASE 1<br>2. EMITTER 2<br>3. COLLECTOR 2<br>4. BASE 2<br>5. EMITTER 1<br>6. COLLECTOR 1 | STYLE 17:<br>PIN 1. BASE 1<br>2. EMITTER 1<br>3. COLLECTOR 2<br>4. BASE 2<br>5. EMITTER 2<br>6. COLLECTOR 1 | STYLE 18:<br>PIN 1. VIN1<br>2. VCC<br>3. VOUT2<br>4. VIN2<br>5. GND<br>6. VOUT1                       |
| STYLE 19:<br>PIN 1. IOUT<br>2. GND<br>3. GND<br>4. V CC<br>5. V EN<br>6. V REF                             | STYLE 20:<br>PIN 1. COLLECTOR<br>2. COLLECTOR<br>3. BASE<br>4. EMITTER<br>5. COLLECTOR<br>6. COLLECTOR | STYLE 21:<br>PIN 1. ANODE 1<br>2. N/C<br>3. ANODE 2<br>4. CATHODE 2<br>5. N/C<br>6. CATHODE 1               | STYLE 22:<br>PIN 1. D1 (i)<br>2. GND<br>3. D2 (i)<br>4. D2 (c)<br>5. VBUS<br>6. D1 (c)                      | STYLE 23:<br>PIN 1. Vn<br>2. CH1<br>3. Vp<br>4. N/C<br>5. CH2<br>6. N/C                                     | STYLE 24:<br>PIN 1. CATHODE<br>2. ANODE<br>3. CATHODE<br>4. CATHODE<br>5. CATHODE<br>6. CATHODE       |
| STYLE 25:<br>PIN 1. BASE 1<br>2. CATHODE<br>3. COLLECTOR 2<br>4. BASE 2<br>5. EMITTER<br>6. COLLECTOR 1    | STYLE 26:<br>PIN 1. SOURCE 1<br>2. GATE 1<br>3. DRAIN 2<br>4. SOURCE 2<br>5. GATE 2<br>6. DRAIN 1      | STYLE 27:<br>PIN 1. BASE 2<br>2. BASE 1<br>3. COLLECTOR 1<br>4. EMITTER 1<br>5. EMITTER 2<br>6. COLLECTOR 2 | STYLE 28:<br>PIN 1. DRAIN<br>2. DRAIN<br>3. GATE<br>4. SOURCE<br>5. DRAIN<br>6. DRAIN                       | STYLE 29:<br>PIN 1. ANODE<br>2. ANODE<br>3. COLLECTOR<br>4. EMITTER<br>5. BASE/ANODE<br>6. CATHODE          | STYLE 30:<br>PIN 1. SOURCE 1<br>2. DRAIN 2<br>3. DRAIN 2<br>4. SOURCE 2<br>5. GATE 1<br>6. DRAIN 1    |

Note: Please refer to datasheet for style callout. If style type is not called out in the datasheet refer to the device datasheet pinout or pin assignment.

|                         |                             |                                                                                                                                                                                     |
|-------------------------|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>DOCUMENT NUMBER:</b> | <b>98ASB42985B</b>          | Electronic versions are uncontrolled except when accessed directly from the Document Repository.<br>Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red. |
| <b>DESCRIPTION:</b>     | <b>SC-88/SC70-6/SOT-363</b> | <b>PAGE 2 OF 2</b>                                                                                                                                                                  |

ON Semiconductor and  are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. ON Semiconductor does not convey any license under its patent rights nor the rights of others.

**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

## PUBLICATION ORDERING INFORMATION

### LITERATURE FULFILLMENT:

Email Requests to: [orderlit@onsemi.com](mailto:orderlit@onsemi.com)

**onsemi Website:** [www.onsemi.com](http://www.onsemi.com)

### TECHNICAL SUPPORT

**North American Technical Support:**

Voice Mail: 1 800-282-9855 Toll Free USA/Canada

Phone: 011 421 33 790 2910

**Europe, Middle East and Africa Technical Support:**

Phone: 00421 33 790 2910

For additional information, please contact your local Sales Representative