



# FFSH40120ADN\_F155

## Silicon Carbide Schottky Diode

### 1200 V, 40 A

#### Features



- Max Junction Temperature 175 °C
- Avalanche Rated 200 mJ
- High Surge Current Capacity
- Positive Temperature Coefficient
- Ease of Paralleling
- No Reverse Recovery / No Forward Recovery

#### Applications

- General Purpose
- SMPS, Solar Inverter, UPS
- Power Switching Circuits

#### Description

SiC Schottky Diode has no switching loss, provides improved system efficiency against Si diodes by utilizing new semiconductor material - Silicon Carbide, enables higher operating frequency, and helps increasing power density and reduction of system size/cost. Its high reliability ensures robust operation during surge or over-voltage conditions



#### Absolute Maximum Ratings $T_C = 25^\circ\text{C}$ unless otherwise noted. (per leg)

| Symbol         | Parameter  | FFSH40120ADN_F155                         | Unit             |   |
|----------------|--|---|------------------|---|
| $V_{RRM}$      | Peak Repetitive Reverse Voltage                                  | 1200                                      | V                |   |
| $E_{AS}$       | Single Pulse Avalanche Energy (Note 1)                           | 200                                       | mJ               |   |
| $I_F$          | Continuous Rectified Forward Current @ $T_C < 148^\circ\text{C}$ | 20* / 40**                                | A                |   |
| $I_{F, Max}$   | Non-Repetitive Peak Forward Surge Current                        | $T_C = 25^\circ\text{C}, 10 \mu\text{s}$  | 1190             | A |
|                |  | $T_C = 150^\circ\text{C}, 10 \mu\text{s}$ | 990              | A |
| $I_{F, SM}$    | Non-Repetitive Forward Surge Current                             | Half-Sine Pulse, $t_p = 8.3 \text{ ms}$   | 135              | A |
| $I_{F, RM}$    | Repetitive Forward Surge Current                                 | Half-Sine Pulse, $t_p = 8.3 \text{ ms}$   | 74               | A |
| $P_{tot}$      | Power Dissipation  | $T_C = 25^\circ\text{C}$                  | 220              | W |
|                |  | $T_C = 150^\circ\text{C}$                 | 37               | W |
| $T_J, T_{STG}$ | Operating and Storage Temperature Range                          | -55 to +175                               | $^\circ\text{C}$ |   |
|                | TO247 Mounting Torque, M3 Screw                                  | 60  | Ncm              |   |

#### Thermal Characteristics

| Symbol          | Parameter                                  | FFSH40120ADN_F155 | Unit               |
|-----------------|--|-------------------|--------------------|
| $R_{\theta JC}$ | Thermal Resistance, Junction to Case, Max. | 0.68* / 0.34**    | $^\circ\text{C/W}$ |

\* Per Leg, \*\* Per Device

FFSH40120ADN\_F155 — Silicon Carbide Schottky Diode

## Package Marking and Ordering Information

| Part Number       | Top Mark     | Package             | Packing Method | Reel Size | Tape Width | Quantity |
|-------------------|--------------|---------------------|----------------|-----------|------------|----------|
| FFSH40120ADN_F155 | FFSH40120ADN | TO-247<br>Long Lead | Tube           | N/A       | N/A        | 30 units |

## Electrical Characteristics $T_C = 25^\circ\text{C}$ unless otherwise noted. (per leg)


| Symbol | Parameter               | Test Conditions                                | Min. | Typ. | Max. | Unit          |
|--------|-------------------------|--|------|------|------|---------------|
| $V_F$  | Forward Voltage         | $I_F = 20\text{ A}, T_C = 25^\circ\text{C}$    | -    | 1.45 | 1.75 | V             |
|        |                         | $I_F = 20\text{ A}, T_C = 125^\circ\text{C}$   | -    | 1.7  | 2    |               |
|        |                         | $I_F = 20\text{ A}, T_C = 175^\circ\text{C}$   | -    | 2    | 2.4  |               |
| $I_R$  | Reverse Current         | $V_R = 1200\text{ V}, T_C = 25^\circ\text{C}$  | -    | -    | 200  | $\mu\text{A}$ |
|        |                         | $V_R = 1200\text{ V}, T_C = 125^\circ\text{C}$ | -    | -    | 300  |               |
|        |                         | $V_R = 1200\text{ V}, T_C = 175^\circ\text{C}$ | -    | -    | 400  |               |
| $Q_C$  | Total Capacitive Charge | $V = 800\text{ V}$                             | -    | 120  | -    | nC            |
| C      | Total Capacitance       | $V_R = 1\text{ V}, f = 100\text{ kHz}$         | -    | 1220 | -    | pF            |
|        |                         | $V_R = 400\text{ V}, f = 100\text{ kHz}$       | -    | 111  | -    |               |
|        |                         | $V_R = 800\text{ V}, f = 100\text{ kHz}$       | -    | 88   | -    |               |

**Notes:**


1: EAS of 200mJ is based on starting  $T_J = 25^\circ\text{C}$ ,  $L = 0.5\text{ mH}$ ,  $I_{AS} = 29\text{ A}$ ,  $V = 150\text{ V}$ .

## Typical Characteristics $T_J = 25^\circ\text{C}$ unless otherwise noted (per leg).


**Figure 1. Forward Characteristics**




**Figure 2. Reverse Characteristics**



**Figure 3. Reverse Characteristics**




**Figure 4. Current Derating**




**Typical Characteristics**  $T_J = 25^\circ\text{C}$  unless otherwise noted (per leg, continue).


**Figure 5. Power Derating**




**Figure 6. Capacitive Charge vs. Reverse Voltage**




**Figure 7. Capacitance vs. Reverse Voltage**



**Figure 8. Capacitance Stored Energy**



**Figure 9. Junction-to-Case Transient Thermal Response Curve**



### Test Circuit and Waveforms

Figure 10. Unclamped Inductive Switching Test Circuit & Waveform



$L = 0.5\text{mH}$


$R < 0.1\Omega$

$V_{DD} = 50\text{V}$

$E_{AVL} = 1/2LI^2 [V_{R(AVL)} / (V_{R(AVL)} - V_{DD})]$

$Q1 = \text{IGBT (}BV_{CES} > DUT V_{R(AVL)}\text{)}$





NOTES: UNLESS OTHERWISE SPECIFIED.

- A. PACKAGE REFERENCE: JEDEC TO-247, ISSUE E, VARIATION AB, DATED JUNE, 2004.
- B. DIMENSIONS ARE EXCLUSIVE OF BURRS, MOLD FLASH, AND TIE BAR EXTRUSIONS.
- C. ALL DIMENSIONS ARE IN MILLIMETERS.
- D. DRAWING CONFORMS TO ASME Y14.5 - 1994

$\triangle E$  DOES NOT COMPLY JEDEC STANDARD VALUE  
 F. DRAWING FILENAME: MKT-TO247G03\_REV02





**TRADEMARKS**

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

- AccuPower™
- AttitudeEngine™
- Awinda®
- AX-CAP®\*
- BitSiC™
- Build it Now™
- CorePLUS™
- CorePOWER™
- CROSSVOL™
- CTL™
- Current Transfer Logic™
- DEUXPEED®
- Dual Cool™
- EcoSPARK®
- EfficientMax™
- ESBC™
- F**™
- Fairchild®
- Fairchild Semiconductor®
- FACT Quiet Series™
- FACT®
- FastvCore™
- FETBench™
- FPS™
- F-PFS™
- FRFET®
- Global Power Resource<sup>SM</sup>
- GreenBridge™
- Green FPS™
- Green FPS™ e-Series™
- Gmax™
- GTO™
- IntelliMAX™
- ISOPLANAR™
- Making Small Speakers Sound Louder and Better™
- MegaBuck™
- MICROCOUPLER™
- MicroFET™
- MicroPak™
- MicroPak2™
- MillerDrive™
- MotionMax™
- MotionGrid®
- MTi®
- MTx®
- MVN®
- mWSaver®
- OptoHiT™
- OPTOLOGIC®
- OPTOPLANAR®
- ®
- Power Supply WebDesigner™
- PowerTrench®
- PowerXS™
- Programmable Active Droop™
- QFET®
- QS™
- Quiet Series™
- RapidConfigure™
- ™
- Saving our world, 1mW/W/kW at a time™
- SignalWise™
- SmartMax™
- SMART START™
- Solutions for Your Success™
- SPM®
- STEALTH™
- SuperFET®
- SuperSOT™-3
- SuperSOT™-6
- SuperSOT™-8
- SupreMOS®
- SyncFET™
- Sync-Lock™
- ®
- TinyBoost®
- TinyBuck®
- TinyCalc™
- TinyLogic®
- TINYOPTO™
- TinyPower™
- TinyPWM™
- TinyWire™
- TranSiC™
- TriFault Detect™
- TRUECURRENT®\*
- μSerDes™
- ™
- UHC®
- Ultra FRFET™
- UniFET™
- VcX™
- VisualMax™
- VoltagePlus™
- XS™
- Xsens™
- 仙童®

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

**DISCLAIMER**

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. TO OBTAIN THE LATEST, MOST UP-TO-DATE DATASHEET AND PRODUCT INFORMATION, VISIT OUR WEBSITE AT [HTTP://WWW.FAIRCHILDSEMI.COM](http://www.fairchildsemi.com). FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

**AUTHORIZED USE**

Unless otherwise specified in this data sheet, this product is a standard commercial product and is not intended for use in applications that require extraordinary levels of quality and reliability. This product may not be used in the following applications, unless specifically approved in writing by a Fairchild officer: (1) automotive or other transportation, (2) military/aerospace, (3) any safety critical application – including life critical medical equipment – where the failure of the Fairchild product reasonably would be expected to result in personal injury, death or property damage. Customer's use of this product is subject to agreement of this Authorized Use policy. In the event of an unauthorized use of Fairchild's product, Fairchild accepts no liability in the event of product failure. In other respects, this product shall be subject to Fairchild's Worldwide Terms and Conditions of Sale, unless a separate agreement has been signed by both Parties.

**ANTI-COUNTERFEITING POLICY**

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Terms of Use

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

**PRODUCT STATUS DEFINITIONS**

**Definition of Terms**

| Datasheet Identification | Product Status        | Definition  |
|--------------------------|-----------------------|---|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.   |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.   |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.  |

Rev. I77